















CHEMWALL SEALS

Materials Technology

The new EMILTEC EUCW Pump marks a turning point in the Self Service Car Wash industry with the introduction of **CHEMWALL** Seals.

The new **CHEMWALL** Seals are the result of an exclusive research and development process conducted in collaboration with our partner, a leader in the production of high-tech hydraulic Seals.

A new production procedure, combined with an innovative material, are the basis of the new **CHEMWALL** Seals for use in EMILTEC EUCW series Pumps.

It assures maximum resistance to the chemical agents used in Self Service Car Wash Systems.

TEMWALL

BENEFITS

Heavy Duty Stainless Steel Structure

Made to last longer thanks to the steel core structure.

Integrated sustaining ring

This special ring prevents extrusion of Seals ensuring longer life.

Extreme Endurance

New polymer resistant to the most aggressive chemicals, reliable also in highly corrosive environments.

Guaranteed durability

CHEMWALL lasts up to 10 times longer than the standard solutions ensuring excellent reliability over time.



SERIE EUCW

PLUNGER PUMP FOR SELF SERVICE CAR WASH SYSTEMS WITH LONG-LIFE SEALS

Durability and innovation: exclusive **CHEMWALL** technology



High resistance to chemicals

The EUCW series is designed following specific needs of Self Service Car Wash systems, including wheel wash chemicals.



UDOR exclusive

CHEMWALL's innovative Seals are available on EMILTEC EUCW Pumps.



Top quality

Each EMILTEC Pump is 100% tested before shipment to ensure total performance and maximum quality.



Longer life time

Installing the EUCW Pump in your systems ensures an average life span up to 10 times longer than standard solutions.



* The duration may vary depending on the type of use and, in particular, on the chemicals used.

AVAILABLE MODELS

EUCW PUMP CAR WASH VERSION

Achieve new standards of performance and reliability for your Self Service Car Wash systems with the new **EUCW Pump** thanks to **CHEMWALL**'s innovative Seals.

Why EUCW?

EMILTEC presents the ultimate solution to common maintenance and downtime problems caused by Seals deterioration in the presence of aggressive chemical cleaners used in Self Service Car Wash systems.

CHEMWALL Seals offer unparalleled performance and exceptional durability.





Find out all the information on the dedicated web page.

Flow rate	MAX Pressure	RPM 1000 and 1450
11 to 21 l/min 2.9 to 5.5 GPM	200 bar 2900 PSI	
		'

			FLOW RATE	PRESSURE	POWER		
CODE	MODEL	RPM	l/min	bar	kW	WEIGHT	POWER TAKE-OFF
14730069	EUCW 13/20 S	1450	12,5	200	4,9	9.1	S – MALE Shaft 24 mm RIGHT
14730070	EUCW 15/20 S	1000 - 1450	10,5 - 15	200	5,7	9.1	
14730071	EUCW 18/20 S	1000 - 1450	12,5 - 18	200	7	9.1	
14730072	EUCW 21/20 S	1000 - 1450	15 - 21	200	7,5	9.1	
14730073	EUCW 13/20 S-L	1450	12,5	200	4,9	9.1	
14730074	EUCW 15/20 S-L	1000 - 1450	10,5 - 15	200	5,7	9.1	
14730075	EUCW 18/20 S-L	1000 - 1450	12,5 - 18	200	7	9.1	
14730076	EUCW 21/20 S-L	1000 - 1450	15 - 21	200	7,5	9.1	



Via Carlo Boetti, 8/B · 42124 Reggio nell'Emilia Tel.: (+39) 0522 941825 / Email: info@emiltec.com C.F. e Partita I.V.A.: 02674440355

www.emiltec.com